



Thesis Title: Design and implementation of RF SQUID Readout Electronics and optimization of the system	Date:2008-07-2
--	----------------

<p>Student Name: Mahsa Shoaran</p> <p>Student Number:83104072</p> <p>Program of Study: Bachelors' degree</p> <p>Field of Study: Electronics</p> <p>Thesis Advisor: Dr. Fardmanesh</p> <p>Thesis Co-Advisor</p> <p>Thesis Consultant:</p> <p>Second Student:Aynaz Vatankhahghadim(83107475)</p> <p>Keywords: Superconductivity, High-Frequency filters, Variable Attenuators, Pin Diode, Feedback Loop</p>	<p>Abstract: Superconducting Quantum Interference Devices (SQUIDs) are the most sensitive Magnetic flux detectors. According to their physical configuration and detection procedure, SQUIDs are divided in to two types, DC SQUIDs and RF SQUIDs. In this project we have implemented and improved a read-out electronic system (in 800MHz to 1.1GHz) for RF SQUID signal detection. In an old project implemented in the Superconductivity laboratory, microstrip filters used were very big. In this project we replaced them with special LC filters. Furthermore, for having variable attenuation, we designed the related circuits instead of using MMICs. At another stage, we designed and completed the feedback loop of the system for FLL RF SQUID detection. At last, for more noise reduction and EMC considerations, we implemented the blocks of the system on a smaller board with proper shieldings.</p>
---	---